

Pressure Hoses & Tubing



Washing Machine Hose



Application

Washing machine water inlet hoses, hot and cold.
Inner wall: black, outer wall: ribbed white

Assemblies are a non stocked item, and minimum order quantities may apply.

Designed for hot and cold water connections to washing machines. Will not mark painted walls or enamelled appliances.

Nominal		Working		Burst		Weight Kg/m	Coil Lengths in Metres
I.D. (mm)	O.D. (mm)	Pres. @ 20°C Mpa	P.S.I.	Pres. @ 20°C Mpa	P.S.I.		
10	17.5	2.0	290	8.0	1,160	0.23	20, 60s, 100, 200r
12.5	20.5	2.0	290	8.0	1,160	0.25	20, 45s, 100, 200r

Lilac Reclaimed Water Hose



Application

Watering parks and gardens with reclaimed water. Also suitable for use as a domestic garden hose. Inner wall: black, outer wall: smooth lilac.

A hose specially formulated for use with reclaimed water. Its Lilac cover complies with the international standard for use with reclaimed water. The hose has "RECLAIMED WATER NOT FOR DRINKING" printed along its length for added safety.

Nominal		Working		Burst		Weight Kg/m	Coil Lengths in Metres
I.D. (mm)	O.D. (mm)	Pres. @ 20°C Mpa	P.S.I.	Pres. @ 20°C Mpa	P.S.I.		
19	25.5	1.0	145	4.0	580	0.27	20, 100
25	34.4	1.0	145	4.0	580	0.60	20, 100

Eva - Beverage Tube



Application

Dispensing beverages, including beer and mixed drinks. Transferring most fluid and semi fluid foodstuffs. Wall: translucent.

Formulated from Ethylene Vinyl Acetate, a food grade compound, it will not taint foodstuffs and beverages. It has good flexibility, a mirror smooth bore and excellent abrasion resistance

Nominal		Working		Weight Kg/m	Coil Lengths in Metres
I.D. (mm)	O.D. (mm)	Pres. @ 20°C Mpa	P.S.I.		
4	7.0	0.28	40	7	100
5	8.0	0.28	40	12	100
6	10.0	0.28	40	16	100
8	12.5	0.28	40	20	100
10	15.0	0.28	40	46	100
12.5	17.5	0.28	40	66	100

Anfo Blast Tube



Wall: black with orange stripe.

For the transfer of ANFO explosives. Conforms to AS2187.2 - 1993

	Nominal		Weight Kg/m	Coil Lengths in Metres
	I.D. (mm)	O.D. (mm)		
Rigid	19	26.0	270	30, 60
	25	33.0	445	30, 60
Flexible	19	26.0	390	30, 60
	25	33.0	642	30, 60



Tubing

PVC ~ Non Toxic ~ Clear



Non toxic tube manufactured to AS2070 1999 with excellent clarity, flexibility and mirror smooth bore for low friction flow.

Application

Suitable for food & beverage fluids, medical drainage and low pressure general delivery lines. Wall: clear.

+ Cafeteria tube

Nominal I.D. (mm)	O.D. (mm)	Working Pres. @ 20°C		Weight Kg/m	Coil Lengths in Metres
		Mpa	P.S.I.		
3	5.0	0.9	125	17	30, 300s
4	7.0	0.8	120	35	30
5	8.0	0.8	115	42	30, 120s
6	9.0	0.6	90	48	30, 100s
8	11.0	0.5	75	61	30, 150s
10	13.0	0.4	60	74	30, 130s
+ 10	15.0	0.6	90	134	30
12.5	15.5	0.5	70	90	30, 90s
16	19.0	0.4	60	113	30, 60s
19	23.0	0.4	50	181	30, 40s
25	31.0	0.4	50	360	30
32	38.0	0.3	40	452	30
38	46.0	0.3	40	712	30
50	60.0	0.3	40	1,165	15

Nylon



Nylon pressure tubing is made from premium quality raw materials and precision engineered to ensure simplicity of connections with fittings and adaptors.

Applications

Pneumatic and hydraulic control systems, fuel tubing, air and gas tubing. Also ideal for handling weed killing solutions, refrigerants, fresh and sea water, fumigants, paints and lacquers and many other products. Wall: Available in black and natural (translucent).

Semi-Rigid available in Black only

	Nominal O.D. (mm)	Wall Thickness (mm)	Working Pres. @ 20°C		Weight Kg/m	Coil Lengths in Metres
			Mpa	P.S.I.		
Flexible Metric	4mm	0.65mm	2.0	290	7.6	100
	5mm	0.85mm	2.0	290	11.8	100
	6mm	1mm	2.0	290	16.6	100
	8mm	1.4mm	2.0	290	30.9	100
	10mm	1.7mm	2.0	290	47.2	100
	12mm	2mm	2.0	290	66.8	100
Flexible Imperial	1/8"	0.019"	1.7	250	4.4	100
	3/16"	0.031"	1.7	250	10.0	100
	1/4"	0.040"	1.7	250	17.7	100
	5/16"	0.049"	1.7	250	26.9	100
	3/8"	0.058"	1.7	250	39.7	100
	1/2"	0.076"	1.7	250	68.6	100
	5/8"	0.065"	0.9	125	80.4	100
	3/4"	0.080"	0.9	125	117.1	100
	Semi Rigid Imperial	3/16"	0.039"	4.3	625	12.5
1/4"		0.050"	4.3	625	21.6	100
5/16"		0.062"	4.3	625	33.8	100
3/8"		0.074"	4.3	625	48.5	100
Self Store	1/2"	0.097"	4.3	625	87.1	100
	6mm	0.8mm	1.2	174	30	
	10mm	1.1mm	1.2	174	30	
	12.5mm	1.6mm	1.2	174	30	